

RUGGED MONITOR



Industrial touch screen monitor,
ready for Automation, Productivity and Logistics applications.



Cost Effective Solution
Wide Monitor range up to 24-inch
Touch Screen Technology
Industrial-grade Protection
HDMI, DVI, VGA ports
Wall, Floor and Desktop Mount

| | | |
|---------------------------------------|---|---|
| Display Touchscreen | 10.1 inch (1280 x 800 resolution, 16:10 widescreen) | Capacitive multi-touch by finger and pen |
| | 11.6 inch (1920 x 1080 resolution, 16:9 widescreen) | Capacitive multi-touch by finger and pen |
| | 13.3 inch (1920 x 1080 resolution, 16:9 widescreen) | Capacitive multi-touch by finger and pen |
| | 15.6 inch (1920 x 1080 resolution, 16:9 widescreen) | Capacitive multi-touch by finger and pen |
| | 18.5 inch (1920 x 1080 resolution, 16:9 widescreen) | Capacitive multi-touch by finger and pen |
| | 21.5 inch (1920 x 1080 resolution, 16:9 widescreen) | Capacitive multi-touch by finger and pen |
| | 23.8 inch (1920 x 1080 resolution, 16:9 widescreen) | Capacitive multi-touch by finger and pen |
| | Audio Keyboard Interfaces | 10.4 inch (1024 x 768 resolution, 4:3) |
| 12 inch (1024 x 768 resolution, 4:3) | | Resistive single-touch by industrial thick gloves |
| 15 inch (1024 x 768 resolution, 4:3) | | Resistive single-touch by industrial thick gloves |
| 17 inch (1280 x 1024 resolution, 5:4) | | Resistive single-touch by industrial thick gloves |
| Dual Speaker and Headphone | | |
| Power button | | |
| HDMI | | x1 |
| DVI | | x1 |
| VGA | | x1 |
| USB | | x1 Type RJ45, touchscreen reserved |
| Power | Audio | x1 Line In 3.5mm |
| | DC In power | x1 |
| | 12-24VDC | |
| Cooling System | AC/DC Power Adapter | Input: 100-240VAC, 50/60Hz, Output: 12VDC, 5A |
| Construction | Fanless design - No fan. No noise. | |
| Mounting | Aluminum alloy, black color RAL9005 | |
| Dimensions | PANEL mount, VESA mount | Open-frame mounting on request *** |
| Weight | Please require the product size by display | |
| Environment ** | approx.5kg (21.5 inch) | |
| | Glass protection | 7H anti-scratch surface |
| | Dust Resistance | IP6x |
| | Water Resistance | IPx5 |
| | Operating Temperature | 0 °C to 50 °C |
| Regulatory | Humidity | 0% to 90% relative humidity, non-condensing |
| | CE, FCC, WEEE, RoHS | |
| Included in the box Accessories * | Power Adapter, Panel-mount Clips, Quick User Guide, Warranty document | |
| | User replaceable film protector screen, Rubber-tipped Pen, | |
| | AC/DC Power Adapter, DC/DC Power Adapter for wide input voltage, | |
| | Desktop Stand, VESA holder to wall, roof or floor mounting. | |

* Optional

** Tested by an independent third-party lab following CE and IEC 60529.

*** Non-Standard Part, assembly by request. A minimum order quantity (MOQ) is required.

Specifications given herein may be changed at any time without any notice.

Copyright © 2024 Sesitek. All Rights Reserved.